ZALAIN
Range of products

Welded Steel Tubes for precision applications

ArcelorMittal

EN10305

Round
(EN10305-2)
Cold Drawn
Welded

Wall Thickness (mm)

Ø (mm)	0,7	0,76	0,8	0,9	1	1,15	1,2	1,21	1,24	1,25	1,27	1,3	1,35	1,4	1,45	1,5	1,6	1,65	1,7	1,71	1,8	1,89	1,9	2	2,01	2,22	2,4	2,5	2,52	2,6	2,7	2,8	2,81	2,85	2,9	2,95	3	3,2	3,3	3,5	3,6	3,7	3,8	3,85	4	4,01	4,2	4,5	4,51	5	5,5	5,9	5,91	6
15																■								■																																
16					■		■									■								■																																
17					■		■									■	■							■				■								■	■	■																		
20			■		■	■	■									■	■				■			■				■								■	■	■																		
25			■		■	■	■									■	■				■			■				■		■						■	■	■	■	■	■	■	■				■		■					
30			■		■	■	■									■	■				■			■				■		■						■	■	■	■	■	■	■	■				■		■					
35			■		■	■	■									■	■				■			■				■		■						■	■	■	■	■	■	■	■	■			■		■					
40			■		■	■	■									■	■				■			■				■		■						■	■	■	■	■	■	■	■	■			■		■					
45			■		■	■	■									■	■				■			■				■		■						■	■	■	■	■	■	■	■	■			■		■					
50			■		■	■	■									■	■				■			■				■		■						■	■	■	■	■	■	■	■	■			■		■					
55			■		■		■									■	■				■			■				■		■						■	■	■	■	■	■	■	■	■			■		■					
60			■		■		■									■	■				■			■				■		■						■	■	■	■	■	■	■	■	■			■		■					
65					■		■									■	■				■			■				■		■						■	■	■	■	■	■	■	■	■			■		■					
70					■											■					■			■				■		■						■	■			■	■	■	■	■			■		■					
75					■											■					■			■				■		■						■				■	■	■	■	■			■							
80																■								■						■							■			■	■	■	■	■										
85																■								■																						■									
90																■								■																						■									
95																								■																						■									
100																								■																																

Round
(EN10305-3)

Wall Thickness (mm)

Ø (mm)	0,5	0,6	0,76	0,8	0,9	1	1,15	1,2	1,21	1,24	1,25	1,27	1,3	1,35	1,4	1,45	1,5	1,6	1,65	1,7	1,71	1,8	1,89	1,9	2	2,01	2,22	2,3	2,4	2,5	2,52	2,6	2,7	2,8	2,81	2,85	2,9	2,95	3	3,2	3,3	3,5	3,6	3,7	3,8	3,85	4	4,01	4,2	4,5	4,51	5	5,5	5,9	5,91	6
16						■		■									■																																								
18																		■																																							
20						■		■		■							■					■			■				■	■									■																			
21																	■																																								
21,3								■																																																	
22															■			■				■			■				■																												
22,2																																																									
24															■																								■																		
25										■	■				■		■	■				■			■					■		■										■	■														
26										■			■									■			■							■								■																		
27																																							■																		
28													■				■								■							■										■			■	■											
30										■							■								■														■			■															
32														■	■		■	■				■			■				■	■		■							■			■																
33																																										■			■				■	■	■						
34																									■																																	
35													■				■	■	■			■			■																		■							■							
38																									■																	■							■								
38,5												■																																													
38,6						■							■				■	■		■	■				■									■																								
40													■																							■												■			■		■	■			■
42																	■								■								■																									
44																		■			■																																					
45						■		■					■		■	■	■	■		■		■			■	■			■			■	■	■								■				■				■						■	■
45,02																									■																															■	
45,4								■																																																	
45,56		■																																																								
46						■																																																				
46,4								■																																																	
48																		■							■						■																■									
48,6								■																																																	
49		■																■																																							
50													■				■					■		■	■				■	■		■		■				■				■	■			■			■			■	■	■	■		■
50,8						■							■					■							■					■		■	■				■		■																		
50,81																														■																											
50,82																									■																																
53,2																		■																																							
53,97						■																																																			
54																	■								■																																
55													■			■	■	■							■		■			■		■	■			■		■	■	■	■	■			■	■											
57																																								■																	
58													■									■								■					■	■		■		■			■				■										
60,0													■				■					■			■	■			■	■		■		■	■		■	■	■		■	■		■		■		■	■		■		■	■	■		■
60,12																							■																																		
63								■					■		■		■	■				■		■	■														■								■										
65													■				■	■				■		■	■													■			■	■	■		■	■			■		■	■			■	■
70													■				■								■					■		■		■							■	■	■			■		■								
73																																																		■							
75									■															■								■							■			■								■							
78													■																			■	■															■									
80											■		■				■								■							■			■		■		■			■																

ArcelorMittal
Tubular Products
24-26 Bd d'Avranches
L-1160 Luxembourg

Web site: tubular.arcelormittal.com
Technical hotline: **constructube@arcelormittal.com**

Our products are proposed with a large number of options, depending on mill:
- Grades: standard E195, E220, E235
- Surface finishing: variable depending on mill
- Length: standard 6 or 12 m, possibility to cut-to-length on request
- Possibility to remove inside weld
- Standard minimum quantity

For more details, please contact us.
Specific demands on request.